This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

0						
· ·						
	rt.	ś				
÷						
;						
			٠			
					;	

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7:

A41B

(11) International Publication Number: WO 00/07468

(43) International Publication Date: 17 February 2000 (17.02.00)

IL

(21) International Application Number: PCT/IL99/00434

(22) International Filing Date: 5 August 1999 (05.08.99)

(30) Priority Data: 125695 7 August 1998 (07.08.98)

(71)(72) Applicant and Inventor: GILOH, Tamar [IL/IL]; Hahistadrut Street 19A, 45270 Hod Hasharon (IL).

(74) Agents: SANFORD, T., Colb et al.; Sanford T. Colb & Co., P.O. Box 2273, 76122 Rehovot (IL).

(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

Without international search report and to be republished upon receipt of that report.

(54) Title: PROTECTIVE UNDERGARMENT

(57) Abstract

A protective undergarment including an integrally formed undergarment body formed of a liquid impermeable material, and an absorptive pad associated with the integrally formed undergarment body.

WO 00/07468 PCT/IL99/00434

PROTECTIVE UNDERGARMENT FIELD OF THE INVENTION

The present invention relates to protective undergarments generally as well as to methods for manufacture thereof.

BACKGROUND OF THE INVENTION

Various types of protective undergarments are known in the patent literature. The following patents and patent applications and the references cited therein are believed to represent the state of the art: U.S. Patent 5,098,419; PCT Published Patent Application WO 96/36248 and European Patent 327,823.

SUMMARY OF THE INVENTION

The present invention seeks to provide a protective undergarment which is generally lighter and more comfortable than conventional protective undergarments and which can be manufactured in large quantities at relatively low cost.

There is thus provided in accordance with a preferred embodiment of the present invention a protective undergarment including an integrally formed undergarment body formed of a liquid impermeable material, and an absorptive pad associated with the integrally formed undergarment body.

Preferably, the undergarment body includes a first portion which is formed with multiple perforations to permit passage of perspiration therethrough, and a second portion which is substantially not perforated, so as to prevent passage of body fluids therethrough.

In accordance with a preferred embodiment of the present invention the absorptive pad is associated with the undergarment body at the second portion.

Preferably, the second portion extends beyond the absorptive pad.

There is additionally provided in accordance with a preferred embodiment of the present invention a protective undergarment comprising an integrally formed undergarment body formed of a liquid impermeable material, the undergarment body including a first portion which is formed with multiple perforations to permit passage of perspiration therethrough, and a second portion which is substantially not perforated, so as to prevent passage of body fluids therethrough.

Preferably, the liquid impermeable material is latex.

Alternatively, the liquid impermeable material is silicone rubber.

In accordance with a preferred embodiment of the present invention, the undergarment body has a thickness of approximately 10 microns.

20

25

30

15

5

10

Preferably, the protective garment also comprises an absorbent pad fixed to the undergarment body.

The protective undergarment may be a brassiere, underpants or any other suitable garment

The protective undergarment may have fibers adhered to at least one surface of the undergarment body

5

10

15

20

25

30

In accordance with one embodiment of the present invention, the absorbent pad includes a portion extending downward from the crotch along the thigh.

There is additionally provided in accordance with a preferred embodiment of the present invention a method of manufacture of protective undergarments comprising the steps of forming an undergarment body of a liquid impermeable material, and forming multiple perforations on a first portion of the undergarment body to permit passage of perspiration therethrough

Preferably, the step of associating an absorbent pad with a second portion of the undergarment body

There is also provided in accordance with a preferred embodiment of the present invention a method of manufacture of protective undergarments comprising the steps of forming an undergarment body of a liquid impermeable material, and fixedly associating an absorbent pad with the undergarment body

Preferably, the associating step comprising forming the undergarment body over a portion of the pad

Preferably, the method also includes the step of forming the undergarment body. over an absorbent pad, so as to fix the pad to the undergarment body.

Additionally in accordance with a preferred embodiment of the present invention, the method includes the step of adhering cotton fibers to at least one surface of the undergarment body

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be understood and appreciated more fully from the following detailed description, taken in conjunction with the drawings in which:

Fig. 1A, 1B, 1C, 1D, 1E, 1F, 1G, 1H and 1I are illustrations of a method for producing protective undergarments in accordance with a preferred embodiment of the present invention; and

Fig. 2 is a simplified illustration of protective undergarments produced generally by the method of Figs. 1A - 1F in accordance with a preferred embodiment of the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENT

5

10

15

20

25

30

Reference is now made to Fig. 1A, 1B, 1C, 1D, 1E, 1F, 1G, 1H and 1I are simplified illustrations of a method for producing protective undergarments in accordance with a preferred embodiment of the present invention. The invention is described hereinbelow with reference to Figs. 1A - 1I, with specific reference to underpants, it being appreciated that the invention applies equally to any other suitable undergarment.

As seen in Fig. 1A, a three dimensional garment form 10 is provided on which an array 12 of protrusions 14, such as needles, is formed in the general shape of underpants to be formed. The crotch area 10 of the underpants is preferably not formed with protrusions 14. The remainder of the form 10 is preferably coated with a non-adhesion substance, such as TEFLON R.

As shown in Fig. 1B, garment form 10 is preferably dipped in a liquid 18, such as latex or silicone, which when allowed to dry, forms a stretchable, light weight garment 18 over array 12 and crotch area 10. It may be appreciated that the provision of protrusions 14 causes the garment 18 to be perforated except at crotch area 16. Thus the garment 18 is "breathable" except at the crotch area 16, where it is liquid impermeable.

In accordance with a preferred embodiment of the present invention, as illustrated in Fig. 1C, an absorptive pad 20 is associated with the light weight garment 18 at the crotch area 16. It may be associated by the use of an adhesive, but is preferably attached to the remainder of garment 18 by virtue of the fact that the liquid is allowed to dry on the form 10 in engagement with the absorptive pad 20.

Prior to removal of the garment 18 from the form 10, the exterior surface of the garment on the form 10, which will eventually be turned inside-out to form the interior surface, is preferably sprayed with adhesive 22, as shown in Fig. 1D and thereafter with cotton fibers 24 or any other suitable material, as indicated in Fig. 1E, thereby to provide a comfortable and non-stick skin engaging surface. Preferably pad 20 is covered during the steps of Figs. 1D and 1E with a cover 26, which extends somewhat beyond the pad, so as to prevent liquid migration from the pad to the cotton fibers.

WO 00/07468 PCT/IL99/00434

The resulting garment 30 may then be removed from the form 10, as seen in Fig. 1F and turned inside out. The outer surface of garment 30 may be coated or otherwise covered with cotton fiber or any other suitable material and finished in an appropriate manner.

The completed garment 40, as seen in Fig. 1G, is preferably extremely light weight, low cost, stretchable, underpants, which is perforated generally except at the crotch area and which is preferably integrally formed with an internal absorptive pad at the crotch area. The garment is preferably formed of an elastic material, such as latex or silicone and has a thickness of less than 10 microns. In accordance with a preferred embodiment of the present invention, as seen in Fig. 1H, a tear region 42 may be incorporated in the garment, such as at a side thereof. This enables ease of removal of the garment, by tearing it at region 42. Once removed the torn, worn garment may be disposed of, as illustrated in Fig. 11.

5

10

15

As can be seen from Fig. 2, the garment may be underpants 50, a brassiere 60, or any other suitable garment. It is noted that the pad 62 of the underpants 50 may have a portion which extends downwardly along the wearer's legs.

It will be appreciated by persons skilled in the art that the present invention is not limited by what has been particularly shown and described hereinabove. Rather the scope of the present invention includes variations and modifications of the various features described in the specification and shown in the drawings which may occur to a person of ordinary skill in the art upon reading the foregoing description and which are not in the prior art.

5 CLAIMS

What is claimed is:

30

- 1. A protective undergarment comprising:
- an integrally formed undergarment body formed of a liquid impermeable material; and
 - an absorptive pad associated with the integrally formed undergarment body.
 - 2. A protective undergarment according to claim 1 wherein said undergarment body includes:
- a first portion which is formed with multiple perforations to permit passage of perspiration therethrough; and
 - a second portion which is substantially not perforated, so as to prevent passage of body fluids therethrough.
 - 3. A protective undergarment according to claim 2 wherein said absorptive pad is associated with said undergarment body at said second portion.
- 15 4. A protective undergarment according to claim 3 wherein said second portion extends beyond said absorptive pad.
 - 5. A protective undergarment comprising an integrally formed undergarment body formed of a liquid impermeable material, the undergarment body including:
- a first portion which is formed with multiple perforations to permit passage of perspiration therethrough; and
 - a second portion which is substantially not perforated, so as to prevent passage of body fluids therethrough.
 - 6. A protective undergarment according to claim 1 wherein said liquid impermeable material is latex.
- 25 7. A protective undergarment according to claim I wherein said liquid impermeable material is silicone rubber.
 - 8. A protective undergarment according to claim 1 wherein said undergarment body has a thickness of approximately 10 microns.
 - 9. A protective undergarment according to claim 5 and also comprising an absorbent pad fixed to the undergarment body.
 - 10. A protective undergarment according to claim 1 wherein said undergarment body is a brassiere.


- A protective undergarment according to claim 1 wherein said undergarment body is underpants.
- 12. A protective undergarment according to claim 1 and also comprising fibers adhered to at least one surface of the undergarment body.
- A protective undergarment according to claim 1 wherein said absorbent pad includes a portion extending downward from the crotch along the thigh.
 - A method of manufacture of protective undergarments comprising the steps of:
 forming an undergarment body of a liquid impermeable material; and
 forming multiple perforations on a first portion of the undergarment body to
 permit passage of perspiration therethrough.

10

15

- 15. A method of manufacture according to claim 14 and including the step of associating an absorbent pad with a second portion of said undergarment body.
- A method of manufacture of protective undergarments comprising the steps of:
 forming an undergarment body of a liquid impermeable material; and
 fixedly associating an absorbent pad with said undergarment body.
- 17. A method according to claim 15 wherein said associating step comprising forming said undergarment body over a portion of said pad.
- A method of manufacture of protective undergarments according to claim 15 wherein said liquid impermeable material is latex.
- 20 19. A method of manufacture of protective undergarments according to claim 15 wherein said liquid impermeable material is silicon rubber.
 - 20. A method of manufacture of protective undergarments according to claim 14 wherein said undergarment body has a thickness of approximately 10 microns.
- A method of manufacture of protective undergarments according to claim 14 and also comprising the step of forming the undergarment body over an absorbent pad, so as to fix the pad to the undergarment body
 - A method of manufacture of protective undergarments according to claim 14 and also comprising adhering cotton fibers to at least one surface of the undergarment body.

WO 00/07468 . PCT/IL99/00434







FIG. 1B








FIG. 1E





4/5






FIG. 11





				•
				,
				i,
				, i
k / **, / , **	to the state of the second section of the	the state of the s	Sometimes of the second	
	~ .			
	÷,		<i>5</i> .	

-

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7:
A61F 13/15, 13/20
(11) International Publication Number: WO 00/07468
(43) International Publication Date: 17 February 2000 (17.02.00)

IL

(21) International Application Number: PCT/IL99/00434

(22) International Filing Date: 5 August 1999 (05.08.99)

(30) Priority Data:

125695 7 August 1998 (07.08.98)

(71)(72) Applicant and Inventor: GILOH, Tamar (ILTL); Hahistadrut Street 19A, 45270 Hod Hasharon (IL).

(74) Agents: SANFORD, T., Colb et al., Sanford T. Colb & Co., P.O. Box 2273, 76122 Rehovot (IL).


(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(88) Date of publication of the international search report: 17 August 2000 (17.08.00)

(54) Title: PROTECTIVE UNDERGARMENT



(57) Abstract

A protective undergarment including an integrally formed undergarment body (18) formed of a liquid impermeable material, and an absorptive pad (20) associated with the integrally formed undergarment body (18).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

		EŞ	Spain	LS	Lesotho	SI	Stovenia
L	Albania	چي Fl	Finland	LT	Lithuania	SK	Slovakia
M	Armenia	FR	France	LU	Luxembourg	SN	Senegal
T	Austria		Gabon	LV	Latvia	SZ	Swaziland
U	Australia	GA	United Kingdom	МС	Monaco	TD	Chad
Z	Azerbaijan	GB		MD	Republic of Moldova	TG	Togo
BA	Bosnia and Herzegovina	GE	Georgia	MG	Madagascar	TJ	Tajikistan
B.	Barbados ,	GH	Ghana	MK	The former Yugoslav	TM	Turkmenistan
E	Belgium	GN	Guinea	,,,,,	Republic of Macedonia	TR	Turkey
3F	Burkina Faso	GR	Greece	ML	Mali	TT	Trinidad and Tobago
3G	Bulgaria	HU	Hungary	MN	Mongolia	UA	Ukraine
ß	Benin	IE	Ireland	MR	Mauritania	UG	Uganda
3R	Brazil	IL	Israel	MW	Malawi	US	United States of Americ
BY	Belarus	IS	Iceland	MX	Mexico	UZ	Uzbekistan
CA	Canada	IT	Italy	NE	Niger	VN	Viet Nam
CF	Central African Republic	JP	Japan	NL	Netherlands	YU	Yugoslavia
CG	Congo	KE	Kenya	NO NO	Norway	zw	Zimbabwe
CH	Switzerland	KG	Kyrgyzstan		New Zealand		•
CI	Côte d'Ivoire	KP	Democratic People's	NZ	Poland		
CM	Cameroon		Republic of Korea	PL			
CN	China	KR	Republic of Korea	PT	Portugal Romania		
CU	Cuba	KZ	Kazakstan	RO	Russian Federation		
CZ	Czech Republic	LC	Saint Lucia	RU			
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden	•	
EE	Estonia	LR	Liberia	SG	Singapore		

INTERNATIONAL SEARCH REPORT

International application No. PCT/IL99/00434

A. CLASSIFICATION OF SUBJECT MATTER IPC(7) : A61F 13/15, 20 US CL. + 604/203						
US CL: 604/393 According to International Patent Classification (IPC) or to both national classification and IPC						
B. FIEL	DS SEARCHED					
Minimum d	ocumentation searched (classification system followed	by classification symbols)				
U.S. :	604/393, 385.07, 394, 395.01, 396; 450/37					
Documentat	ion searched other than minimum documentation to the	extent that such documents are included i	n the fields searched			
Electronic o	Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)					
C. DOC	UMENTS CONSIDERED TO BE RELEVANT					
Category*	Citation of document, with indication, where ap	propriate, of the relevant passages	Relevant to claim No.			
X	US 5,149,336 A (CLARKE et al.) 22 col. 7, lines 45-55.	1, 10, 12, 16				
x	RE 35,687 A (IGUAE et al.) 09 Decen lines 45-56 and col. 3, lines 60-63.	1-9, 11-22				
X	US 2,796,064 A (GREEN et al.) 18 Jun lines 15-20 and 52-60.	1-9, 11-22				
X	US 4,589,876 A (VAN TILBURG) 20	1-9, 11-22				
Purther documents are listed in the continuation of Box C. See patent family annex.						
• Special categories of cited documents: "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention						
to be of particular relevance "E" carrier document published on or after the international filing date considered novel or cannot be considered to involve an inventive such as the property of the propert						
C1 35	ocument which may throw doubts on priority claum(s) or which is ted to establish the publication date of another citation or other secial reason (as specified)	"Y" document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is				
oombined with one or more other such documents, so document published prior to the international filing date but later than one of the same patent family						
Pr. document published prior to the international filing date but later than the priority date claimed Date of the actual completion of the international search Date of mailing of the international search report						
31 MAY 2000						
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Authorized officer						
Box PCT Washington, D.C. 20231						